## CHAPTER 40

## STANDARDS AND SPECIFICATIONS FOR THE STICKERS OR DECALS USED

## BY COUNTIES, CITIES AND TOWNS IN LIEU OF LICENSE PLATES

- 19 VAC 30-40-10. Purpose.
- 19 VAC 30-40-20. Size.
- 19 VAC 30-40-30. Placement.
- 19 VAC 30-40-10. Purpose.

The purpose of this standard is to establish specifications for the size and placement location of stickers or decals used by Counties, Cities, and Towns in lieu of license plates.

19 VAC 30-40-20. Size.

The size of the sticker or decal shall not exceed three inches in height and three inches in length. The shape of the sticker or decal is optional.

19 VAC 30-40-30. Placement.

The sticker or decal shall be placed on <u>at</u> the <u>bottom of the</u> windshield adjacent to the right side of the official inspection sticker when viewed through the windshield from inside the vehicle. The top edge of the sticker or decal shall not extend upwards more than three inches from the bottom of the windshield. The side edge adjacent to the official inspection sticker shall not be more than 1/4 inch from the edge of the official inspection sticker.

At the option of the motor vehicle's owner, the sticker or decal may be affixed at the upper edge of the center lower left corner of the windshield so that the inside or left edge of the sticker or decal is within one inch of the extreme left edge of the windshield when looking through the windshield from inside the vehicle. When placed

at this location, the bottom edge of the sticker or decal must be affixed within three inches of the bottom of the windshield.