# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

# 9 VAC 25-180-10. Definitions.

The words and terms used in this chapter shall have the meanings defined in the State Water Control Law (§ 62.1-44.2 et seq. of the Code of Virginia) and 9 VAC 25-31 (VPDES Permit Regulation) unless the context clearly indicates otherwise, except that for the purposes of this chapter:

"Commencement of construction" means the initial disturbance of soils associated with clearing, grading, or excavating activities or other construction activities.

"Construction activity" means any clearing, grading or excavation associated with large construction activity, or associated with small construction activity.

"Control measure" means any best management practice or other method used to prevent or reduce the discharge of pollutants to surface waters.

"Final stabilization" means that one of the following situations has occurred:

1. All soil disturbing activities at the site have been completed and a permanent vegetative cover has been established on denuded areas not otherwise permanently stabilized. Permanent vegetation shall not be considered established until a ground cover is achieved that is uniform, mature enough to survive, and will inhibit erosion.

2. For individual lots in residential construction, final stabilization can occur by either:

a. The homebuilder completing final stabilization as specified in subdivision 1 of this definition; or

b. The homebuilder establishing temporary stabilization, including perimeter controls for an individual lot prior to occupation of the home by the homeowner, and informing the homeowner of the need for, and benefits of, final stabilization.

3. For construction projects on land used for agricultural purposes (e.g., pipelines across crop or range land), final stabilization may be accomplished by returning the disturbed land to its preconstruction agricultural use. Areas disturbed that were not previously used for agricultural activities, such as buffer strips immediately adjacent to surface waters, and areas which are not being returned to their preconstruction agricultural use must meet the final stabilization criteria specified in subdivision 1 or 2 of this definition.

"Large construction activity" means construction activity including clearing, grading and excavation except operations that result in the disturbance of less than five acres of total land area. Large construction activity also includes the disturbance of less than five acres of total land area that is a part of a larger common plan of development or sale if the larger common plan will ultimately disturb five acres or more.

"Municipal separate storm sewer" means a conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains): (i) owned or operated by a state, city, town, borough, county, parish, district, association, or other public body (created by or pursuant to state law) having jurisdiction over disposal of sewage, industrial wastes, storm water, or other wastes, including special districts under state law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or a designated and approved management agency under § 208 of the Clean Water Act (CWA) (33 USC § 1251 et seq.) that discharges to surface waters of the state; (ii) designed or used for collecting or conveying storm water; (iii) that is not a combined sewer; and (iv) that is not part of a POTW.

"Operator" means, in the context of storm water associated with construction activity, any person associated with a construction project that meets either of the following two criteria: (i) the person has direct operational control over construction plans and specifications, including the ability to make modifications to those plans and specifications or (ii) the person has day-to-day operational control of those activities at a project which are necessary to ensure compliance with a storm water pollution prevention plan for the site or other permit conditions (i.e., they are authorized to direct workers at a site to carry out activities required by the storm water pollution prevention plan or comply with other permit conditions).

"Permittee" means any operator whose construction site is covered under this general permit.

"Point source" means any discernible, confined, and discrete conveyance, including but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, landfill leachate collection system, vessel or other floating craft from which pollutants are or may be discharged. This term does not include return flows from irrigated agriculture or agricultural storm water runoff.

"Runoff coefficient" means the fraction of total rainfall that will appear at the conveyance as runoff.

"Small construction activity" means construction activity including clearing, grading, and excavating that results in land disturbance of equal to or greater than one acre and less than five acres. Small construction activity also includes the disturbance of less than one acre of total land area that is part of a larger common plan of development or sale if the larger

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

common plan will ultimately disturb equal to or greater than one and less than five acres. Small construction activity does not include routine maintenance that is performed to maintain the original line and grade, hydraulic capacity, or original purpose of the facility.

"Storm water" means storm water runoff, snow melt runoff, and surface runoff and drainage.

"Storm water discharge associated with construction activity" means a discharge of pollutants in storm water runoff from areas where soil disturbing activities (e.g., clearing, grading, or excavation); construction materials or equipment storage or maintenance (e.g., fill piles, borrow area, concrete truck washout, fueling); or other industrial storm water directly related to the construction process (e.g., concrete or asphalt batch plants) are located.

### 9 VAC 25-180-20. Purpose.

This general permit regulation governs storm water discharges from construction activities. For the purposes of this chapter, these discharges are defined as storm water discharges associated with large construction activity, and storm water discharges associated with small construction activity. Storm water discharges associated with other types of industrial activity shall not have coverage under this general permit. This general permit covers only discharges through a point source to a surface water or through a municipal or nonmunicipal separate storm sewer system to surface waters. Storm water discharges associated with industrial activity that originate from the site after construction activities have been completed and the site has undergone final stabilization are not authorized by this permit.

## 9 VAC 25-180-40. Effective date of the permit.

This general permit will become effective on July 1, 2004. The general permit will expire on June 30, 2009.

## 9 VAC 25-180-50. Authorization to discharge.

A. Any operator governed by this general permit is authorized by this to discharge to surface waters of the Commonwealth of Virginia provided that the operator files a complete and accurate registration statement in accordance with 9 VAC 25-180-60, any fees required by 9 VAC 25-20, complies with the requirements of 9 VAC 25-180-70, and provided that:

1. The operator shall not have been required to obtain an individual permit according to 9 VAC 25-31-170 B;

2. The operator shall not be authorized by this general permit to discharge to state waters specifically named in other board regulations or policies which prohibit such discharges;

3. Prior to commencing construction, the operator shall obtain approval of an erosion and sediment control plan from the locality in which the construction activity is to occur or from another appropriate plan approving authority authorized under the Erosion and Sediment Control Regulations, (4 VAC 50-30), unless the operator receives an "agreement in lieu of a plan" from the locality, or is exempt from the requirement to submit an erosion and sediment control plan by 4 VAC 50-30;

4. Storm water discharges which the director determines cause, may reasonably be expected to cause, or contribute to a violation of water quality standards are not covered by this permit;

5. The storm water discharge authorized by this permit may be combined with other sources of storm water which are not required to be covered under a VPDES permit, so long as the combined discharge is in compliance with this permit. Any discharge authorized by a different VPDES permit may be commingled with discharges authorized by this permit; and

6. Discharges to waters for which a "total maximum daily load" (TMDL) allocation for sediment or a parameter that addresses sediment (such as total suspended solids, turbidity, or siltation) has been established by the board and approved by EPA are not eligible for coverage under this permit unless the storm water pollution prevention plan (SWPPP) developed by the operator incorporates measures and controls that are consistent with the assumptions and requirements of such TMDL. To be eligible for coverage under this general permit, the SWPPP must incorporate any conditions applicable to discharges from the construction site that are necessary for consistency with the assumptions and requirements of the TMDL. If a specific wasteload allocation has been established that would apply to discharges from the construction site, the operator must incorporate that allocation into the SWPPP and implement necessary steps to meet that allocation.

B. This permit may also be used to authorize storm water discharges from support activities (e.g., concrete or asphalt batch plants, equipment staging yards, material storage areas, excavated material disposal areas, borrow areas) located on-site or offsite provided that:

1. The support activity is directly related to a construction site that is required to have VPDES permit coverage for discharges of storm water associated with construction activity;

2. The support activity is not a commercial operation serving multiple unrelated construction projects by different operators, and does not operate beyond the completion of the construction activity at the last construction project it supports; and

3. Appropriate controls and measures are identified in a storm water pollution prevention plan covering the discharges from the support activity areas.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

C. Support activities located off-site are not required to be covered under this general permit. Discharges of storm water from off-site support activities may be authorized under another VPDES permit. Where storm water discharges from off-site support activities are not authorized under this general permit, the land area of the off-site support activity need not be included in determining the total land disturbance acreage of the construction activity seeking general permit coverage.

D. Receipt of this general permit does not relieve any operator of the responsibility to comply with any other applicable federal, state or local statute, ordinance or regulation.

E. The board may waive the otherwise applicable requirements in this general permit regulation for a storm water discharge from small construction activity where storm water controls are not needed based on a "total maximum daily load" (TMDL) established by the board and approved by EPA that addresses the pollutants of concern or, for nonimpaired waters that do not require TMDLs, an equivalent analysis that determines allocations for small construction sites for the pollutants of concern or that determines that such allocations are not needed to protect water quality based on consideration of existing in stream concentrations, expected growth in pollutant contributions from all sources, and a margin of safety. For the purpose of this section, the pollutants of concern include sediment or a parameter that addresses sediment (such as total suspended solids, turbidity or siltation) and any other pollutant that has been identified as a cause of impairment of any water body that will receive a discharge from the construction activity. In order to obtain this waiver, prior to the commencement of construction the operator must certify to the board that the construction activity will take place, and storm water discharges will occur, within the drainage area addressed by a TMDL, or within the drainage area addressed by an equivalent analysis.

### 9 VAC 25-180-55. Qualifying state, tribal and local programs.

Qualifying state, tribal, or local erosion and sediment control program requirements may be incorporated by reference into the Storm Water Pollution Prevention Plan (SWPPP) required by 9 VAC 25-180-70 of this permit. Where a qualifying state, tribal, or local program does not include one or more of the elements in this section, then the permittee must include those elements as part of the SWPPP required by 9 VAC 25-180-70 of this permit. A qualifying state, tribal, or local erosion and sediment control program is one that includes:

1. Requirements for construction site operators to implement appropriate erosion and sediment control best management practices;

2. Requirements for construction site operators to control waste such as discarded building materials, concrete truck washout, chemicals, litter, and sanitary waste at the construction site that may cause adverse impacts to water quality;

3. Requirements for construction site operators to develop and implement an SWPPP. (An SWPPP includes site descriptions, descriptions of appropriate control measures, copies of approved state, tribal or local requirements, maintenance procedures, inspection procedures); and

4. Requirements to submit a site plan for review that incorporates consideration of potential water quality impacts.

# 9 VAC 25-180-60. Registration statement.

A. Deadlines for submitting registration statement.

1. Except as provided in subdivision 3 of this subsection, operators must submit a complete and accurate registration statement in accordance with the requirements of this section prior to the commencement of construction activities (i.e., the initial disturbance of soils associated with clearing, grading, excavation activities, or other construction activities).

2. For storm water discharges from construction projects where the operator changes, including instances where an operator is added after a registration statement has been submitted, the new operator must submit a complete and accurate registration statement prior to assuming operational control over site specifications or commencing work on site.

3. In order to continue permit coverage, operators of ongoing construction activity projects as of July 1, 2004, that received authorization to discharge for those projects under the construction storm water general permit issued in 1999 must:

a. Submit a complete and accurate registration statement by July 1, 2004; and

b. Update their storm water pollution prevention plan to comply with the requirements of this general permit within 30 days after the date of coverage under this general permit.

4. Effective date of permit coverage. The operator of a construction activity is authorized to discharge storm water from those construction activities under the terms and conditions of this permit immediately upon submission of a complete and accurate registration statement to DEQ, but in no event earlier than the effective date of this permit, except as noted in subdivision 3 of this subsection. For the purposes of this regulation, a registration statement that is mailed is considered to be submitted once it is postmarked. Operators are not authorized to discharge if the registration statement is incomplete or incorrect, or if the discharge(s) was not eligible for coverage under this permit.

5. Late notifications. Operators are not prohibited from submitting registration statements after initiating clearing, grading, excavation activities, or other construction activities. When a late registration statement is submitted, authorization for

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

discharges occurs no earlier than the submission date of the registration statement. The department reserves the right to take enforcement action for any unpermitted discharges or permit noncompliance that occurs between the commencement of construction and discharge authorization.

B. Registration statement. The operator shall submit a registration statement which shall contain the following information:

1. Name, mailing address and telephone number of the construction activity operator (NOTE: The permit will be issued to this operator, and the certification in subdivision 13 of this subsection must be signed by the appropriate person associated with this operator);

2. Name and location of the construction activity and all off-site support activities to be covered under the permit. If a street address is unavailable, provide latitude and longitude;

3. Status of the activity: federal, state, public, or private;

4. Nature of the construction project (e.g., commercial, industrial, residential, agricultural, oil and gas, etc.);

5. Name of the receiving water(s);

6. If the discharge is through a municipal separate storm sewer system (MS4), the name of the municipal operator of the storm sewer;

7. Estimated project start date and completion date;

8. Total land area of development and estimated area to be disturbed by construction activity (to the nearest quarter acre);

9. Whether the area to be disturbed by the construction activity is part of a larger common plan of development or sale;

10. A topographic map or other map that clearly shows the location of the construction activity, the area to be disturbed (including off-site support activities), and the receiving stream or streams for the storm water discharges;

NOTE: A storm water pollution prevention plan (SWPPP) must be prepared in accordance with the requirements of the VPDES General Permit for Storm Water Discharges from Construction Activities prior to submitting this registration statement. By signing this registration statement you are certifying that the SWPPP has been prepared;

11. The location of where the SWPPP may be viewed, and the name and phone number of a contact person (NOTE: The contact person should be a person knowledgeable in the principles and practice of erosion and sediment controls, such as a licensed professional engineer, responsible land disturber (RLD), or other knowledgeable person who possesses the skills to assess conditions at the construction site that could impact storm water quality); and

12. A list of the permanent BMPs (both structural and nonstructural) that will be installed at the construction activity site. For each BMP that will be installed, include the following information:

- a. Type of permanent BMP to be installed;
- b. Geographic location (county state Hydrologic Unit Code);
- c. Waterbody the BMP will discharge into;
- d. Number of acres that will be treated (to the nearest quarter acre).

13. The following certification: "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is to the best of my knowledge and belief true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment for knowing violations."

C. The registration statement shall be signed in accordance with 9 VAC 25-180-70, Part III K.

D. Where to submit. The registration statement shall be submitted to the DEQ regional office that serves the area where the construction activity is located.

## 9 VAC 25-180-65. Termination of permit coverage.

A. Requirements. The operator of the construction activity may only submit a notice of terminationafter one or more of the following conditions have been met:

1. Final stabilization has been achieved on all portions of the site for which the operator is responsible;

2. Another operator has assumed control over all areas of the site that have not been finally stabilized;

3. Coverage under an alternative VPDES permit has been obtained; or

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

4. For residential construction only, temporary stabilization has been completed and the residence has been transferred to the homeowner.

The notice of termination must be submitted within 30 days of one of the above conditions being met. Authorization to discharge terminates seven days after the notice of termination is submitted. For the purposes of this regulation, a notice of termination that is mailed is considered to be submitted once it is postmarked.

B. Notice of termination.

The notice of termination shall contain the following information:

1. Name, mailing address and telephone number of the construction activity operator.

2. Name and location of the construction activity. If a street address is unavailable, provide latitude and longitude.

3. The VPDES storm water general permit number.

4. The basis for submission of the notice of termination, including:

a. Final stabilization has been achieved on all portions of the site for which the operator is responsible;

b. Another operator has assumed control over all areas of the site that have not been finally stabilized;

c. Coverage under an alternative VPDES permit has been obtained; or

d. For residential construction only, temporary stabilization has been completed and the residence has been transferred to the homeowner.

5. The following certification: "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is to the best of my knowledge and belief true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment for knowing violations."

C. The notice of termination shall be signed in accordance with 9 VAC 25-180-70, Part III K.

D. Where to submit. The notice of termination shall be submitted to the DEQ regional office that serves the area where the construction activity is located.

# 9 VAC 25-180-70. General permit.

Any operator whose registration statement is accepted by the director will receive the following permit and shall comply with the requirements in it and be subject to all requirements of the VPDES Permit Regulation (9 VAC 25-31).

General Permit No.: VAR10

Effective Date: July 1, 2004 Expiration Date: June 30, 2009

#### GENERAL PERMIT FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

# AUTHORIZATION TO DISCHARGE UNDER THE VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM AND THE VIRGINIA STATE WATER CONTROL LAW

In compliance with the provisions of the Clean Water Act, as amended, and pursuant to the State Water Control Law and regulations adopted pursuant to that, operators of construction activities (those sites or common plans of development or sale that will result in the disturbance of one or more acres of total land area) with storm water discharges from these construction activities are authorized to discharge to surface waters within the boundaries of the Commonwealth of Virginia, except those specifically named in board regulation or policies which prohibit such discharges.

The authorized discharge shall be in accordance with this cover page, Part I - Discharge Authorization and Special Conditions, Part II - Storm Water Pollution Prevention Plan, and Part III - Conditions Applicable To All VPDES Permits as set forth herein.

PART-I DISCHARGE AUTHORIZATION AND SPECIAL CONDITIONS

A. Coverage under this permit.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

1. During the period beginning with the date of coverage under this general permit and lasting until the permit's expiration date, the permittee is authorized to discharge storm water from construction activities.

2. This permit also authorizes storm water discharges from off-site support activities (e.g., concrete or asphalt batch plants, equipment staging yards, material storage areas, excavated material disposal areas, borrow areas) provided that:

a. The support activity is directly related to a construction site that is required to have VPDES permit coverage for discharges of storm water associated with construction activity;

b. The support activity is not a commercial operation serving multiple unrelated construction projects by different operators, and does not operate beyond the completion of the construction activity at the last construction project it supports; and

c. Appropriate controls and pollution prevention measures for the discharges from the support activity areas are identified in the storm water pollution prevention plan required for the construction activity under Part II D of this permit.

3. There shall be no discharge of floating solids or visible foam in other than trace amounts.

B. Limitation on coverage.

1. Post-construction discharges. This permit does not authorize storm water discharges that originate from the site after construction activities have been completed and the site, including any temporary support activity site, has undergone final stabilization. Post-construction industrial storm water discharges may need to be covered by a separate VPDES permit.

2. Discharges mixed with nonstorm water. This permit does not authorize discharges that are mixed with sources of nonstorm water, other than those discharges which are identified in Part I D 2 (Exceptions to prohibition of nonstorm water discharges) and are in compliance with Part II D 5 (Nonstorm water discharge management).

3. Discharges covered by another permit. This permit does not authorize storm water discharges associated with construction activity that have been covered under an individual permit or required to obtain coverage under an alternative general permit in accordance with Part III X.

4. TMDL limitation. Discharges to waters for which a "total maximum daily load" (TMDL) allocation for sediment or a parameter that addresses sediment (such as total suspended solids, turbidity, or siltation) has been established by the board and approved by EPA are not eligible for coverage under this permit unless the storm water pollution prevention plan (SWPPP) developed by the operator incorporates measures and controls that are consistent with the assumptions and requirements of such TMDL. To be eligible for coverage under this general permit, the SWPPP must incorporate any conditions applicable to discharges from the construction site that are necessary for consistency with the assumptions and requirements of the TMDL. If a specific wasteload allocation has been established that would apply to discharges from the allocation into the SWPPP and implement necessary steps to meet that allocation.

C. Commingled discharges. Any discharge authorized by a different VPDES permit may be commingled with discharges authorized by this permit.

D. Prohibition of nonstorm water discharges.

1. Except as provided in Parts I A 2, I C and I D 2, all discharges covered by this permit shall be composed entirely of storm water associated with construction activity.

2. The following nonstorm water discharges from active construction sites are authorized by this permit provided the nonstorm water component of the discharge is in compliance with Part II D 5 (Nonstorm water discharges):

a. Discharges from fire fighting activities;

b. Fire hydrant flushings;

c. Waters used to wash vehicles where detergents are not used;

d. Water used to control dust;

e. Potable water sources, including waterline flushings;

f. Water used for hydrostatic testing of new pipeline construction;

g. Routine external building wash down which does not use detergents;

h. Pavement washwaters where spills or leaks of toxic or hazardous materials have not occurred (unless all spilled material has been removed) and where detergents are not used;

i. Uncontaminated air conditioning or compressor condensate;

j. Uncontaminated ground water or spring water;

k. Foundation or footing drains where flows are not contaminated with process materials such as solvents;

I. Uncontaminated excavation dewatering, and

m. Landscape irrigation.

E. Releases of hazardous substances or oil in excess of reportable quantities.

The discharge of hazardous substances or oil in the storm water discharges from the construction site shall be prevented or minimized in accordance with the storm water pollution prevention plan for the site. This permit does not relieve the permittee of the reporting requirements of 40 CFR Part 110 (2002), 40 CFR Part 117 (2002) and 40 CFR Part 302 (2002) or § 62.1-44.34:19 of the Code of Virginia.

Where a release containing a hazardous substance or oil in an amount equal to or in excess of a reportable quantity established under either 40 CFR Part 110 (2002), 40 CFR Part 117 (2002) or 40 CFR Part 302 (2002) occurs during a 24-hour period:

1. The permittee is required to notify the department in accordance with the requirements of Part III G as soon as he has knowledge of the discharge;

2. Where a release enters a municipal separate storm sewer system (MS4), the permittee shall also notify the owner of the MS4; and

3. The storm water pollution prevention plan required under Part II D of this permit must be reviewed to identify measures to prevent the reoccurrence of such releases and to respond to such releases, and the plan must be modified where appropriate.

#### F. Spills.

This permit does not authorize the discharge of hazardous substances or oil resulting from an on-site spill.

G. Termination of permit coverage.

1. The operator of the construction activity may only submit a notice of termination after one or more of the following conditions have been met:

a. Final stabilization has been achieved on all portions of the site for which the operator is responsible;

b. Another operator has assumed control over all areas of the site that have not been finally stabilized;

c. Coverage under an alternative VPDES permit has been obtained; or

d. For residential construction only, temporary stabilization has been completed and the residence has been transferred to the homeowner.

2. The notice of termination must be submitted within 30 days of one of the conditions in Part I G 1 being met. Authorization to discharge terminates seven days after the notice of termination is submitted.

3. The notice of termination shall be signed in accordance with Part III K of this permit.

H. Water quality protection. The permittee must select, install, implement and maintain best management practices (BMPs) at the construction site that minimize pollutants in the discharge as necessary to meet applicable water quality standards. If there is evidence indicating that the storm water discharges authorized by this permit are causing, have the reasonable potential to cause, or are contributing to an excursion above an applicable water quality standard, or are causing downstream pollution (as defined in § 62.1-44.3 of the Code of Virginia), the board may take appropriate enforcement action, may require the permittee to include and implement appropriate controls in the SWPPP to correct the problem, and/or may require the permittee to obtain an individual permit in accordance with 9 VAC 25-31-170 B 3.

# PART II STORM WATER POLLUTION PREVENTION PLAN

A storm water pollution prevention plan (SWPPP) shall be developed and implemented for the construction activity covered by this permit. SWPPPs shall be prepared in accordance with good engineering practices. The SWPPP shall identify potential sources of pollution which may reasonably be expected to affect the quality of storm water discharges from the construction site. In addition, the SWPPP shall describe and ensure the implementation of practices which will be used to reduce pollutants in storm water discharges from the construction site, and to assure compliance with the terms and conditions of this permit.

The SWPPP requirements of this general permit may be fulfilled by incorporating by reference other state, tribal or local plans such as an erosion and sediment control (ESC) plan, a spill prevention control and countermeasure (SPCC) plan developed for the site under § 311 of the federal Clean Water Act or best management practices (BMP) programs otherwise required for the facility provided that the incorporated plan meets or exceeds the SWPPP requirements of Part II D. If an erosion and sediment control plan for the construction activity is being incorporated by reference, the referenced plan must be approved by the locality

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

in which the construction activity is to occur or by another appropriate plan approving authority authorized under the Erosion and Sediment Control Regulations (4 VAC 50-30) prior to the commencement of construction. All plans incorporated by reference into the SWPPP become enforceable under this permit. If a plan incorporated by reference does not contain all of the required elements of the SWPPP of Part II D, the permittee must develop the missing elements and include them in the required SWPPP.

Once a definable area has been finally stabilized, the operator may mark this on the SWPPP and no further SWPPP or inspection requirements apply to that portion of the site (e.g., earth disturbing activities around one of three buildings in a complex are done and the area is finally stabilized; one mile of a roadway or pipeline project is done and finally stabilized, etc.).

The operator must implement the SWPPP as written from commencement of construction activity until final stabilization is complete.

A. Deadlines for SWPPP preparation and compliance.

1. The SWPPP shall be prepared prior to submittal of the registration statement and provide for compliance with the terms and schedule of the plan beginning with the initiation of construction activities.

 For ongoing construction activity involving a change of operator, the new operator shall accept and maintain the existing SWPPP, or prepare and implement a new SWPPP prior to taking over operations at the site.

B. Signature, plan review and making plans available.

1. The SWPPP shall be signed in accordance with Part III K.

2. The SWPPP shall be retained, along with a copy of this permit at the construction site from the date of commencement of construction activity to the date of final stabilization. Permittees with day-to-day operation control over SWPPP implementation shall have a copy of the plan available at a central location on-site for the use of all operators and those identified as having responsibilities under the plan whenever they are on the construction site. The SWPPP must be made available, in its entirety, to the department for review at the time of an on-site inspection.

3. The permittee shall make SWPPPs available upon request to the department; a state or local agency approving sediment and erosion plans, grading plans, or storm water management plans; local government officials; or the operator of a municipal separate storm sewer system receiving discharges from the site.

C. Maintaining an updated SWPPP.

1. The permittee shall amend the SWPPP whenever there is a change in design, construction, operation, or maintenance that has a significant effect on the discharge of pollutants to surface waters and that has not been previously addressed in the SWPPP.

2. The SWPPP must be amended if during inspections or investigations by site staff, or by local, state or federal officials, it is determined that the discharges are causing water quality exceedances, or the SWPPP is ineffective in eliminating or significantly minimizing pollutants in storm water discharges from the construction site.

3. Based on the results of an inspection, the SWPPP must be modified as necessary to include additional or modified BMPs designed to correct problems identified. Revisions to the SWPPP must be completed within seven calendar days following the inspection. Implementation of these additional or modified BMPs must be accomplished as described in Part II D 3 b.

4. The SWPPP must clearly identify for each measure identified in the plan, the contractor(s) or subcontractor(s) that will implement the measure. The SWPPP shall be amended to identify any new contractor that will implement a measure of the plan.

D. Storm water pollution prevention plan contents.

The SWPPP shall include the following items:

1. Site and activity description. Each SWPPP shall provide the following information:

a. A description of the nature of the construction activity, including the function of the project (e.g., low density residential, shopping mall, highway, etc.);

b. The intended sequence and timing of activities that disturb soils at the site (e.g., grubbing, excavation, grading, utilities and infrastructure installation).

c. Estimates of the total area expected to be disturbed by excavation, grading, or other construction activities including offsite borrow and fill areas;

d. A description of any other potential pollution sources, such as vehicle fueling, storage of fertilizers or chemicals, sanitary waste facilities, etc.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

e. Identification of the nearest receiving waters at or near the construction site that will receive discharges from disturbed areas of the project;

f. The location and description on any discharge associated with industrial activity other than construction at the site. This includes storm water discharges from dedicated asphalt plants and dedicated concrete plants that are covered by this permit.

g. A site map indicating:

(1) Directions of storm water flow and approximate slopes anticipated after major grading activities;

(2) Areas of soil disturbance and areas of the site which will not be disturbed;

(3) Locations of major structural and nonstructural controls identified in the SWPPP, including those that will be permanent controls that will remain after construction activities have been completed;

(4) Locations where stabilization practices are expected to occur;

(5) Surface water bodies (including wetlands);

(6) Locations where storm water discharges to a surface water;

(7) Locations of off-site material, waste, borrow or equipment storage areas covered by the plan;

(8) Locations of other potential pollution sources, such as vehicle fueling, storage of chemicals, sanitary waste facilities, etc.; and

(9) Areas where final stabilization has been accomplished and no further construction-phase permit requirements apply.

2. Controls to reduce pollutants. The SWPPP shall include a description of all pollution control measures that will be implemented as part of the construction activity to control pollutants in storm water discharges. For each major activity identified in the project description, the SWPPP shall clearly describe appropriate control measures, the general sequencing during the construction process in which the measures will be implemented, and which operator is responsible for the control measure's implementation.

a. Erosion and sediment controls.

(1) Stabilization practices. The SWPPP shall include a description of interim and permanent stabilization practices for the site. Site plans should ensure that existing vegetation is preserved where attainable and that disturbed portions of the site are stabilized. Stabilization practices may include, but are not limited to: temporary seeding, permanent seeding, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, preservation of mature vegetation, riprap, gabions, facines, biologs and other appropriate measures. Use of impervious surfaces for stabilization should be avoided.

(a) A record of the dates when major grading activities occur, when construction activities temporarily or permanently cease on a portion of the site, and when stabilization measures are initiated shall be maintained and included in the SWPPP.

(b) Except as provided in Part II D 2 a (1) (c), (d) and (e), stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, but in no case more than seven days after the construction activity in that portion of the site has temporarily or permanently ceased.

(c) Where the initiation of stabilization measures by the seventh day after construction activity temporary or permanently ceased is precluded by snow cover or frozen ground conditions, stabilization measures shall be initiated as soon as practicable.

(d) Where construction activity on a portion of the site is temporarily ceased, and earth disturbing activities will be resumed within 30 days, temporary stabilization measures do not have to be initiated on that portion of the site.

(e) In drought-stricken areas where initiating perennial vegetative stabilization measures is not possible within seven days after construction activity has temporarily or permanently ceased, final vegetative stabilization measures shall be initiated as soon as practicable.

(2) Structural practices. The SWPPP shall include a description of structural practices to divert flows from exposed soils, retain/detain flows or otherwise limit runoff and the discharge of pollutants from exposed areas of the site. Such practices may include, but are not limited to: silt fences, earth dikes, drainage swales, sediment traps, check dams, subsurface drains, pipe slope drains, level spreaders, storm drain inlet protection, rock outlet protection, reinforced soil retaining systems, gabions, and temporary or permanent sediment basins. Structural practices should be located on upland soils to the degree attainable. The department encourages the use of a combination of sediment and erosion control measures in order to achieve maximum pollutant removal.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

(a) Sediment basins: For common drainage locations that serve an area with three or more acres disturbed at one time, a temporary (or permanent) sediment basin providing 3,618 cubic feet of storage per acre drained, or equivalent control measures, shall be provided where attainable until final stabilization of the site. The 3,618 cubic feet of storage area per acre drained does not apply to flows from off site areas and flows from on-site areas that are either undisturbed or have undergone final stabilization where such flows are diverted around both the disturbed area and the sediment basin. In determining whether installing a sediment basin is attainable, the permittee may consider factors such as site soils, slope, available area on site, etc. In any event, the permittee must consider public safety, especially as it relates to children, as a design factor for the sediment basin and alternative sediment controls shall be used where site limitations would preclude a safe design.

(b) For drainage locations which serve three or more acres at one time and where a temporary sediment basin or equivalent controls is not attainable, smaller sediment basins and/or sediment traps should be used. At a minimum, silt fences, vegetative buffer strips, or equivalent sediment controls are required for all down slope boundaries, and for those side slope boundaries deemed appropriate as dictated by individual site conditions.

(c) For drainage locations serving less than three acres, smaller sediment basins or sediment traps or both should be used. At a minimum, silt fences, vegetative buffer strips or equivalent sediment controls are required for all downslope boundaries, and for those side slope boundaries deemed appropriate as dictated by individual site conditions, of the construction area unless a sediment basin providing storage for 3,618 cubic feet of storage per acre drained is provided.

b. Management practices.

(1) All control measures must be properly selected, installed, and maintained in accordance with manufacturer specifications and good engineering practices. If periodic inspections or other information indicates a control has been used inappropriately, or incorrectly, the permittee must replace or modify the control for site situations as soon as practicable.

(2) If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize off-site impacts.

(3) Litter, construction debris, and construction chemicals exposed to storm water shall be prevented from becoming a pollutant source in storm water discharges.

c. Storm water management.

(1) The SWPPP shall include a description of all post-construction storm water management measures that will be installed during the construction process to control pollutants in storm water discharges after construction operations have been completed. Structural measures should be placed on upland soils to the degree attainable. Such measures must be designed and installed in accordance with applicable local and/or state requirements.

(2) Such measures may include, but are not limited to: storm water detention structures (including dry ponds); storm water retention structures; flow attenuation by use of open vegetated swales and natural depressions; infiltration of runoff onsite; storm water wetlands; sand filters; bioretention systems; water quality structures; and sequential systems (which combine several practices). The SWPPP shall include an explanation of the technical basis used to select the practices to control pollution where flows exceed predevelopment levels.

(3) Velocity dissipation devices shall be placed at discharge locations and along the length of any outfall channel to provide a nonerosive flow velocity from the structure to a water course so that the natural physical and biological characteristics and functions are maintained and protected (e.g., no significant changes in the hydrological regime of the receiving water).

### d. Other controls.

(1) The SWPPP shall describe measures to prevent the discharge of solid materials, including building materials, garbage, and debris to surface waters of the state, except as authorized by a Clean Water Act § 404 permit.

(2) Where construction vehicle access routes intersect paved public roads, provisions shall be made to minimize the transport of sediment by vehicular tracking onto the paved surface. Where sediment is transported onto a public road surface, the road shall be cleaned thoroughly at the end of each day. Sediment shall be removed from the roads by shoveling or sweeping and transported to a sediment control disposal area. Street washing shall be allowed only after sediment is removed in this manner.

(3) The SWPPP shall ensure and demonstrate compliance with applicable state or local waste disposal, sanitary sewer or septic system regulations.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

(4) The SWPPP shall include a description of construction and waste materials expected to be stored on-site with updates as appropriate. The plan shall also include a description of controls to reduce pollutants from these materials, including storage practices to minimize exposure of the materials to storm water, and for spill prevention and response.

(5) The SWPPP shall include a description of pollutant sources from areas other than construction (including storm water discharges from dedicated asphalt plants and dedicated concrete plants), and a description of controls and measures that will be implemented at those sites to minimize pollutant discharges.

#### e. Applicable state or local programs.

The SWPPP shall be consistent with all applicable state or local requirements for soil and erosion control and storm water management including updates to the SWPPP as necessary to reflect any revisions to applicable state or local requirements for soil and erosion control.

#### 3. Maintenance of controls.

a. The SWPPP must include a description and schedule of procedures to maintain in good and effective operating conditions vegetation, erosion and sediment control measures and other protective measures during construction identified in the site plan. If site inspections required by Part II D 4 identify BMPs that are not operating effectively, maintenance shall be performed before the next anticipated storm event, or as soon as practicable to maintain the continued effectiveness of storm water controls.

b. If existing BMPs need to be modified or if additional BMPs are necessary for any reason, implementation shall be completed before the next anticipated storm event. If implementation before the next anticipated storm event is impracticable, the situation shall be documented in the SWPPP and alternative BMPs shall be implemented as soon as practicable.

c. Sediment must be removed from sediment traps or sedimentation ponds when design capacity has been reduced by 25%.

4. Inspections. Inspections by qualified personnel must be conducted of all areas of the site disturbed by construction activity, and areas used for storage of materials that are exposed to storm water. "Qualified personnel" means a person knowledgeable in the principles and practice of erosion and sediment controls, such as a licensed professional engineer, responsible land disturber (RLD), or other knowledgeable person who possesses the skills to assess conditions at the construction site that could impact storm water quality, and to assess the effectiveness of any sediment and erosion control measures selected to control the quality of storm water discharges from the construction activity.

a. Inspections shall be conducted at least once every 14 calendar days and within 48 hours of the end of any runoff producing storm event. Where areas have been finally or temporarily stabilized or runoff is unlikely due to winter conditions (e.g., the site is covered with snow or ice, or frozen ground exists) such inspections shall be conducted at least once every month.

b. Inspectors must look for evidence of, or the potential for, pollutants entering the storm water conveyance system. Erosion and sediment control measures identified in the SWPPP shall be observed to ensure proper operation. Discharge locations where accessible shall be inspected to ascertain whether erosion control measures are effective in preventing significant impacts to receiving waters. Where discharge locations are inaccessible, nearby downstream locations shall be inspected to the extent that such inspections are practicable. Locations where vehicles enter or exit the site shall be inspected for evidence of off-site sediment tracking.

c. Utility line installation, pipeline construction, and other examples of long, narrow, linear construction activities may limit the access of inspection personnel to the areas described in Part II D 4 b. Inspection of these areas could require that vehicles compromise temporarily or even permanently stabilized areas, cause additional disturbance of soils, and increase the potential for erosion. In these circumstances, controls must be inspected on the same frequencies as other construction projects, but representative inspections may be performed. For representative inspections, personnel must inspect controls along the construction site for 0.25 miles above and below each access point where a roadway, undisturbed right-of-way, or other similar feature intersects the construction site and allows access to the areas described above. The conditions of the controls along each inspected 0.25 mile segment may be considered as representative of the condition of controls along that reach extending from the end of the 0.25 mile segment to either the end of the next 0.25 mile segment, or to the end of the project, whichever occurs first. Inspection locations must be listed in the report required by Part II D 4 e.

d. Based on the results of the inspection, the site and activity description identified in the plan in accordance with Part II D 1 of this permit and pollution prevention measures identified in the SWPPP in accordance with Part II D 2 of this permit shall be revised as appropriate within seven calendar days following the inspection.

e. A report summarizing the scope of the inspection, names and qualifications of personnel making the inspection, the dates of the inspection, major observations relating to the implementation of the SWPPP, and actions taken in accordance with

Part II D 4 d of the permit shall be made and retained as part of the SWPPP in accordance with Part III B of this permit. Major observations should include:

(1) The location(s) of discharges of sediment or other pollutants from the site;

(2) Location(s) of BMPs that need to be maintained;

(3) Location(s) of BMPs that failed to operate as designed or proved inadequate for a particular location;

(4) Location(s) where additional BMPs are needed that did not exist at the time of inspection; and

(5) Corrective action required including any changes to the SWPPP that are necessary and implementation dates.

The reports shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with Part III K of this permit.

5. Nonstorm water discharge management. The SWPPP shall identify all allowable sources of nonstorm water discharges listed in Part I D 2 of this permit that are combined with storm water discharges from the construction activity at the site, except for flows from fire fighting activities. The SWPPP shall identify and ensure the implementation of appropriate pollution prevention measures for the nonstorm water components of the discharge.

PART III CONDITIONS APPLICABLE TO AII VPDES PERMITS

NOTE: Monitoring is not required for this permit. If you choose to monitor your storm water discharges or BMPs, you must comply with the requirements of subsections A, B, and C, as appropriate.

A. Monitoring.

1. Samples and measurements taken as required by this permit shall be representative of the monitored activity.

2. Monitoring shall be conducted according to procedures approved under 40 CFR Part 136 or alternative methods approved by the U.S. Environmental Protection Agency, unless other procedures have been specified in this permit.

3. The permittee shall periodically calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals that will ensure accuracy of measurements.

#### B. Records.

1. Records of monitoring information shall include:

a. The date, exact place, and time of sampling or measurements;

b. The individual(s) who performed the sampling or measurements;

c. The date(s) and time(s) analyses were performed;

d. The individual(s) who performed the analyses;

e. The analytical techniques or methods used; and

f. The results of such analyses.

2. Except for records of monitoring information required by this permit related to the permittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years, the permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the registration statement for this permit, for a period of at least three years from the date of the sample, measurement, report or request for coverage. This period of retention shall be extended automatically during the course of any unresolved litigation regarding the regulated activity or regarding control standards applicable to the permittee, or as requested by the board.

### C. Reporting monitoring results.

1. The permittee shall submit the results of the monitoring required by this permit not later than the 10th day of the month after monitoring takes place, unless another reporting schedule is specified elsewhere in this permit. Monitoring results shall be submitted to the department's regional office.

2. Monitoring results shall be reported on a discharge monitoring report (DMR) or on forms provided, approved or specified by the department.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

3. If the permittee monitors any pollutant specifically addressed by this permit more frequently than required by this permit using test procedures approved under 40 CFR Part 136 or using other test procedures approved by the U.S. Environmental Protection Agency or using procedures specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or reporting form specified by the department.

4. Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in this permit.

D. Duty to provide information. The permittee shall furnish to the department, within a reasonable time, any information which the board may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The board may require the permittee to furnish, upon request, such plans, specifications, and other pertinent information as may be necessary to determine the effect of the wastes from his discharge on the quality of state waters, or such other information as may be necessary to accomplish the purposes of the State Water Control Law. The permittee shall also furnish to the department, upon request, copies of records required to be kept by this permit.

E. Compliance schedule reports. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

F. Unauthorized discharges. Except in compliance with this permit or another permit issued by the board, it shall be unlawful for any person to:

1. Discharge into state waters sewage, industrial wastes, other wastes, or any noxious or deleterious substances; or

2. Otherwise alter the physical, chemical or biological properties of such state waters and make them detrimental to the public health, or to animal or aquatic life, or to the use of such waters for domestic or industrial consumption, or for recreation, or for other uses.

G. Reports of unauthorized discharges. Any permittee who discharges or causes or allows a discharge of sewage, industrial waste, other wastes or any noxious or deleterious substance into or upon state waters in violation of Part III F, or who discharges or causes or allows a discharge that may reasonably be expected to enter state waters in violation of Part III F, shall notify the department of the discharge immediately upon discovery of the discharge, but in no case later than 24 hours after said discovery. A written report of the unauthorized discharge shall be submitted to the department within five days of discovery of the discharge. The written report shall contain:

1. A description of the nature and location of the discharge;

2. The cause of the discharge;

3. The date on which the discharge occurred;

4. The length of time that the discharge continued;

5. The volume of the discharge;

6. If the discharge is continuing, how long it is expected to continue;

7. If the discharge is continuing, what the expected total volume of the discharge will be; and

8. Any steps planned or taken to reduce, eliminate and prevent a recurrence of the present discharge or any future discharges not authorized by this permit.

Discharges reportable to the department under the immediate reporting requirements of other regulations are exempted from this requirement.

H. Reports of unusual or extraordinary discharges. If any unusual or extraordinary discharge including a bypass or upset should occur from a treatment works and the discharge enters or could be expected to enter state waters, the permittee shall promptly notify, in no case later than 24 hours, the department by telephone after the discovery of the discharge. This notification shall provide all available details of the incident, including any adverse effects on aquatic life and the known number of fish killed. The permittee shall reduce the report to writing and shall submit it to the department within five days of discovery of the discharge in accordance with Part III 1.2. Unusual and extraordinary discharges include but are not limited to any discharge resulting from:

1. Unusual spillage of materials resulting directly or indirectly from processing operations;

- 2. Breakdown of processing or accessory equipment;
- 3. Failure or taking out of service some or all of the treatment works; and
- 4. Flooding or other acts of nature.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

I. Reports of noncompliance. The permittee shall report any noncompliance which may adversely affect state waters or may endanger public health.

1. An oral report shall be provided within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information which shall be reported within 24 hours under this paragraph:

a. Any unanticipated bypass; and

b. Any upset which causes a discharge to surface waters.

2. A written report shall be submitted within five days and shall contain:

a. A description of the noncompliance and its cause;

b. The period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and

c. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

The board may waive the written report on a case-by-case basis for reports of noncompliance under Part III Lif the oral report has been received within 24 hours and no adverse impact on state waters has been reported.

3. The permittee shall report all instances of noncompliance not reported under Part III I 1 or 2 in writing at the time the next monitoring reports are submitted. The reports shall contain the information listed in Part III I 2.

NOTE: The immediate (within 24 hours) reports required in Part III G, H and I may be made to the department's regional office. Reports may be made by telephone or by fax. For reports outside normal working hours, leaving a recorded message shall fulfill the immediate reporting requirement. For emergencies, the Virginia Department of Emergency Management maintains a 24 hour telephone service at 1-800-468-8892.

J. Notice of planned changes.

1. The permittee shall give notice to the department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:

a. The permittee plans an alteration or addition to any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:

(1) After promulgation of standards of performance under § 306 of the federal Clean Water Act which are applicable to such source; or

(2) After proposal of standards of performance in accordance with § 306 of the Clean Water Act which are applicable to such source, but only if the standards are promulgated in accordance with § 306 within 120 days of their proposal;

b. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to offluent limitations nor to notification requirements specified elsewhere in this permit; or

c. The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.

2. The permittee shall give advance notice to the department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

#### K. Signatory requirements.

1. Registration statement. All registration statements shall be signed as follows:

a. For a corporation: by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means: (i) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy-making or decision-making functions for the corporation; or (ii) the manager of one or more manufacturing, production, or operating facilities, provided the manager is authorized to make management decisions that govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;

b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

c. For a municipality, state, federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a public agency includes: (i) the chief executive officer of the agency or (ii) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency.

2. Reports, etc. All reports required by permits and other information requested by the board shall be signed by a person described in Part III K 1 or by a duly authorized representative of that person. A person is a duly authorized representative only if:

a. The authorization is made in writing by a person described in Part III K 1;

b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. A duly authorized representative may thus be either a named individual or any individual occupying a named position; and

c. The written authorization is submitted to the department.

3. Changes to authorization. If an authorization under Part III K 2 is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part III K 2 shall be submitted to the department prior to or together with any reports or information to be signed by an authorized representative.

4. Certification. Any person signing a document under Part III K 1 or 2 shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

L. Duty to comply. The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the State Water Control Law and the Clean Water Act, except that noncompliance with certain provisions of this permit may constitute a violation of the State Water Control Law but not the Clean Water Act. Permit noncompliance is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.

The permittee shall comply with effluent standards or prohibitions established under § 307(a) of the Clean Water Act for toxic pollutants and with standards for sewage sludge use or disposal established under § 405(d) of the Clean Water Act within the time provided in the regulations that establish these standards or prohibitions or standards for sewage sludge use or disposal, even if this permit has not yet been modified to incorporate the requirement.

M. Duty to reapply. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall submit a new registration statement at least 90 days before the expiration date of the existing permit, unless permission for a later date has been granted by the board. The board shall not grant permission for registration statements to be submitted later than the expiration date of the existing permit.

N. Effect of a permit. This permit does not convey any property rights in either real or personal property or any exclusive privileges, nor does it authorize any injury to private property or invasion of personal rights, or any infringement of federal, state or local law or regulations.

O. State law. Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any other state law or regulation or under authority preserved by § 510 of the Clean Water Act. Except as provided in permit conditions on "bypassing" (Part III U), and "upset" (Part III V) nothing in this permit shall be construed to relieve the permittee from civil and criminal penalties for noncompliance.

P. Oil and hazardous substance liability. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under §§ 62.1-44.34:14 through 62.1-44.34:23 of the State Water Control Law.

Q. Proper operation and maintenance. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes effective plant performance, adequate funding, adequate staffing, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of this permit.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

R. Disposal of solids or sludges. Solids, sludges or other pollutants removed in the course of treatment or management of pollutants shall be disposed of in a manner so as to prevent any pollutant from such materials from entering state waters.

S. Duty to mitigate. The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

T. Need to halt or reduce activity not a defense. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

#### U. Bypass.

1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to ensure efficient operation. These bypasses are not subject to the provisions of Part III U 2 and 3.

#### 2. Notice.

a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, prior notice shall be submitted, if possible at least 10 days before the date of the bypass.

b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Part III I.

#### 3. Prohibition of bypass.

a. Bypass is prohibited, and the board may take enforcement action against a permittee for bypass unless:

(1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;

(2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and

(3) The permittee submitted notices as required under Part III U 2.

b. The board may approve an anticipated bypass, after considering its adverse effects, if the board determines that it will meet the three conditions listed in Part III U 3 a.

### V. Upset.

1. An upset constitutes an affirmative defense to an action brought for noncompliance with technology-based permit effluent limitations if the requirements of Part III V 2 are met. A determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is not a final administrative action subject to judicial review.

2. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs or other relevant evidence that:

a. An upset occurred and that the permittee can identify the cause(s) of the upset;

b. The permitted facility was at the time being properly operated;

c. The permittee submitted notice of the upset as required in Part III I; and

d. The permittee complied with any remedial measures required under Part III S.

3. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

W. Inspection and entry. The permittee shall allow the director, or an authorized representative, upon presentation of credentials and other documents as may be required by law to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;

2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and

4. Sample or monitor at reasonable times, for the purposes of ensuring permit compliance or as otherwise authorized by the Clean Water Act and the State Water Control Law, any substances or parameters at any location.

# 9 VAC 25-180-10 et seq. - GENERAL VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM (VPDES) PERMIT REGULATION FOR DISCHARGES OF STORM WATER FROM CONSTRUCTION ACTIVITIES

For purposes of this section, the time for inspection shall be deemed reasonable during regular business hours, and whenever the facility is discharging. Nothing contained herein shall make an inspection unreasonable during an emergency.

X. Permit actions. Permits may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

Y. Transfer of permits.

1. Permits are not transferable to any person except after notice to the department. Except as provided in Part III Y 2, a permit may be transferred by the permittee to a new owner or operator only if the permit has been modified or revoked and reissued, or a minor modification made, to identify the new permittee and incorporate such other requirements as may be necessary under the State Water Control Law and the Clean Water Act.

2. As an alternative to transfers under Part III Y 1, this permit may be automatically transferred to a new permittee if:

a. The current permittee notifies the department at least 30 days in advance of the proposed transfer of the title to the facility or property;

b. The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them; and

c. The board does not notify the existing permittee and the proposed new permittee of its intent to modify or revoke and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in Part III Y 2 b.

Z. Severability. The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances and the remainder of this permit shall not be affected thereby.

# FORMS

Department of Environmental Quality, Water Division, Permit Application Fee (rev. 7/02).

VPDES General Permit Registration Statement - Construction Activity Storm Water Discharges , (VAR10), SWGP-VAR10-RS (rev. 7/04).

VPDES General Permit Notice of Termination - Construction Activity Storm Water Discharges , (VAR10), SWGP-VAR10-NOT (rev. 7/04).

CERTIFIED TRUE AND ACCURATE: \_

Robert G. Burnley Director, DEQ

DATE: \_\_\_\_\_